



Lacq Decking Oil

Lacq Decking Oil protects the wooden decking in your garden against discoloration and weathering for an extended period of time, protects the wood against mould, algae and fungal attacks in a natural way. Lacq Decking Oil is made with premium quality natural vegetable oils and waxes.

Lacq Non-slip Decking Oil is very suitable for the annual maintenance of wooden decking, ramps etc. This product can be used on almost any type of wood. Lacq Decking Oil is easy to use and the application of just one layer is normally sufficient. Enriches the natural wood colour and makes it water repellent.

Preparation

- When the wood is already aged & weathered, use Lacq Turbogel as a pre-treatment to revitalize the wood.
- The wooden substrate must be completely dry and free from dust, grease or oil. Remove any loose or flaking timber.
- Any previously applied coatings must be completely removed
- Always test the product on an inconspicuous area first.

Application

- Stir Lacq Decking Oil thoroughly before use.
- Apply a thin layer using brush or roller suited for solvent based paint.
- Always apply in the direction of the wood grain.
- Allow the product to work for 10-15 minutes. Then remove any excess oil using a lint free cloth.

Caution!

Make sure you wipe off the excess oil on the surface using a lint free cloth.

If this step is not completed, the surface may stay tacky or leave glossy spots.

After every oil treatment, wipe off any excess oil until the surface feels hand dry.

Afterwards

- Clean the used tools with solvent.
- Close the lid properly and store it in upright position
- To avoid any risk of fire, ensure that any used soiled rags are disposed responsibly. Preferably in an airtight container or doused with water.

Warning: To avoid any risk of fire, ensure that any used soiled rags are disposed responsibly. Preferably in an airtight container or doused with water.