



# Lacq Deckingoil

Lacq Deckingoil protects your (hard) wooden decking parts against weathering, makes it water-repellent and enriches the wood color. Lacq Deckingoil is composed of high-quality vegetable oils and waxes and is therefore maximally impregnating. This prevents the growth of algae and fungi. Lacq Deckingoil is very easy to use and you are done in just 1 layer.

## Applicable on (hard) wood:

- Deck
- Terraces
- Fences

## Processing:

1. Allow the deckingoil to reach room temperature. Process between 9 °C and 25 °C.
2. Remove all existing paint and stain layers first.
3. First graying grayed wood with Lacq Turbogel.
4. Always clean and degrease the wood before treatment with deckingoil. Use for this purpose Fluxaf Pro-Clean or Fluxaf Power-Clean.
5. Stir well from the bottom.
6. Use a flat brush or roller suitable for solvent-based paint.
7. Apply the oil lengthwise to the wood for a good finish. Work in zones or shelf by shelf.
8. Let the oil soak in for 10-15 minutes.
9. To prevent layer thickness build-up, scrub the excess oil with a lint-free one cloth until the wood surface feels dry to the touch.
10. If there are still "chapped" spots after drying, repeat the treatment.
11. Avoid layer thickness build-up: If you do not boil off the excess oil, there can be shiny and/or sticky spots appear on the wood.

*Pay attention! Duration of wood protection depends on the quality of the wood, proper pre-treatment, painting, maintenance and intensity of load.*

*Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.*

## Coverage:

About 10-15 m<sup>2</sup> per liter.

*Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.*

## Drying time:

Dust dry: approx. 1 hour.  
Recoatable after: approx. 8 hours.

*Pay attention! Drying times depend on the applied layer and the ambient temperature. Optimal conditions are 20 °C.*

## Cleaning:

Clean tools with turpentine and seal airtight and turn around to fill the rim for a good seal.

*Pay attention! There is a risk of scalding and fire with the textiles used. Always pour over with water and allow to dry thoroughly.*

## Available quantities:

1L, 2,5L & 20L.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

**Available colors:**

Natural & Bankirai.

*Pay attention! The type of wood and the number of layers applied can influence the color result. We therefore recommend that you always set up a test piece first, so that you can get the result judge.*

**Shelf life:**

2 years in original unopened packaging, frost-free, in a dry place (temperature between 5 °C and 35 °C). Avoid freezing during transport and storage.

**Safety information:**

For detailed safety information, please consult the MSDS.

MSDS is available on [www.lacq.eu](http://www.lacq.eu).