



Lacq Produra

Lacq Produra is a durable and high quality protector for all wooden surfaces. Produra contains very little solvents and is made out of natural components like vegetable oil and water. Thanks to the unique composition Produra nourishes the wood from within. It provides a translucent stain, which remains flexible so it will not crack, peel or blister even in severe exterior weather conditions. Produra allows the wood to breathe, does not yellow and remains true to colour thanks to the highly resistant UV-filter.

Applicable to/on:

- Fencing
- Shed
- Veranda
- Garden furniture
- Other outdoor wood

Processing:

1. The surface must be dry, free of dust and grease. Remove loose parts. Sanding is not only when a smooth result is desired.
2. Stir Produra well before use.
3. Apply with a flat brush, roller or spray, for a good finish Produra in the lengthwise of the wood grain.
4. Second coat can only be applied after complete drying for about 6 hours. We advise
5. Apply 2-3 layers to untreated wood.

Pay attention! Wear protective gloves, clothing, eye protection and face protection.

Keep out of reach of children. Always put on a sample first to see if you get the desired finish. This can differ per wood type.

Coverage:

About 16 m² per liter.

Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.

Drying time:

Dust dry:	approx. 6 hours.
Recoat after:	approx. 6 hours.
Min. processing temperature:	5 °C.
Max. processing temperature:	35 °C.

Cleaning:

Clean tools with water.

Pay attention! Avoid release into the environment.

Available quantities:

1L, 2,5L, & 20L.

Available colors:

Naturel, Brown, Teak, White, Old Grey, Grey, Anthracite, Black, Olive, Green Clay, White Clay & Blue Clay.

Shelf life:

2 years in original unopened packaging, frost-free, in a dry place (temperature between 5 °C and 35 °C). Avoid freezing during transport and storage.

Safety information:

For detailed safety information, please consult the MSDS. MSDS is available on www.lacq.eu.