



Lacq Teak Oil

Lacq offers the right wood protection for every job! Lacq Teak Oil is an authentic recipe based on various vegetable oils for annual protection and maintenance of wooden garden furniture. It protects hardwoods such as teak and bankirai for a long time against soiling or ageing, is very easy to apply and preserves the natural wood colour.

Applicable To:

- Garden wood
- Garden furniture

Suitable For:

- Hardwood
- Teak wood
- Bankirai wood
- Other soft- & hardwood species

Application On Untreated Wood:

1. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Sanding is not necessary, only when a smooth result is desired.
2. First clean greyed wood with [Lacq Wood Degreaser](#).
3. Clean with [Fluxaf Pro-Clean](#).
4. Stir the contents thoroughly.
5. Use a flat brush, roller or lint-free cloth. Apply in the longitudinal direction of the wood grain for a good finish.
6. Apply first coat. On highly absorbent substrates a second coat can be applied wet-on-wet.
7. Leave to penetrate for twenty minutes and remove excess oil with a lint-free cloth, also clean screw, and nail holes well.
8. Building up layer thickness on the substrate should be avoided.
9. If, after complete drying, you still see 'chapped' spots in the wood because it is not fully saturated, repeat the treatment.

Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance, and intensity of load. Always put a test piece on first to see if you get the desired finish. After all, this can vary from one type of wood to another.

Surface Maintenance:

To make the best use of the paintwork, the surface should be cleaned and maintained annually. The surface can be cleaned by gently wiping it. Use a damp cleaning cloth or soft sponge for this purpose. Rough brushing and strong detergents should be avoided.

Tools:

Flat brush or roller suitable for solvent-based paint and a lint-free cloth.

Coverage:

Approximately 6-9 m² per litre.

Coverage always depends on the structure, porosity of the wood, layer thickness, the tools used and application conditions.

Drying Time:

Dust-dry:	Approx. 6 hours
Paintable:	Approx. 16 hours
Min. working temperature:	5 °C.
Max. processing temperature:	25 °C.

Cleaning:

Clean tools with white spirit.

Available Quantities:

750 ml.

Finish:

Matt.

Available Colours:

Transparent.

Please note! The type of wood and the number of coats applied may influence the colour result. We therefore recommend always putting on a test piece first to assess the result.

Shelf Life:

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

Safety Advice:

Keep out of the reach of children. For detailed safety information, refer to the MSDS. MSDS can be downloaded at www.lacq.eu.

Customised advice:

For any advice, please contact the technical team on 0344 633 336.