



# Lacq Wood Degreaser

Lacq offers the right wood protection for every job! Lacq Wood Degreaser is a powerful, gel-based cleaner for de-greying aged and weathered exterior wood. The gel formula allows for deep interior cleaning of wood on both horizontal and vertical sections. No pressure washer is needed, so the wood will not be damaged!

## Applicable To:

- Sheds
- Decking
- Scaffolding
- Garden furniture
- Canopies
- Conservatories
- Fences
- Garden sheds

## Suitable For:

- Douglas wood
- Larch wood
- Hardwood
- Pine wood
- Oak wood
- Scaffolding wood

## Application On Untreated Wood:

1. Protect metals and plants from direct contact and cover them with foil.
2. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Sanding is not necessary.
3. Moisten the surface to be treated with water.
4. Stir the contents thoroughly.
5. Use a flat brush or roller. Apply in the longitudinal direction of the wood grain for a good finish.
6. Apply the gel generously.
7. Let it set for at least 20 minutes.
8. Brush the surface with a hard brush or broom and rinse with water. We do not recommend using a high-pressure cleaner as the hard jet can damage the wood.
9. After complete drying for at least 48 hours, the cleaned surface can be treated with a Lacq product of your choice.

*Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance, and intensity of load. Always do a test area first to see if you get the desired finish and this will vary on different wood.*

## Surface Maintenance:

To make best use of the paintwork, the surface should be cleaned and maintained annually. The surface can be cleaned by gently wiping it. Use a damp cleaning cloth or soft sponge for this purpose. Rough brushing and strong detergents should be avoided.

## Tools:

Flat (disposable) brush.

## Coverage:

Approximately 10 m<sup>2</sup> per litre.

*Coverage always depends on the structure, suction of the wood, layer thickness, the tools used and application conditions.*

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

**Drying Time:**

Paintable:	Approx. .48 hours
Min. working temperature:	9 °C.
Max. processing temperature:	25 °C.

**Contents:**

Lacq Wood Degreaser contains biodegradable oxalic acid (<10%). The product is free of solvents, formaldehyde, chlorine compounds and amines.

**Available Quantities:**

1 litre & 2.5 litres.

**Shelf Life:**

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

**Safety Advice:**

Keep out of the reach of children. For detailed safety information, refer to the MSDS. MSDS can be downloaded at [www.lacq.eu](http://www.lacq.eu).

**Customised advice:**

For any advice, please contact the technical team on 0344 633 336.