



# Lacq Pure Linseed Oil Stain

Lacq offers the right wood protection for every job! Lacq Pure Linseed Oil Stain is an authentic linseed oil protectant for all wooden surfaces with a silk gloss finish. Prepared according to traditional methods. The combination of wood oil and linseed oil ensures optimal results. Due to this unique composition of raw materials, the stain layer remains flexible for a long time so that it does not crack on wood. It nourishes the wood from within and provides long-term protection for up to 6 years!

## Applicable To:

- Sheds
- Fences
- Conservatories
- Canopies
- Garden sheds
- Sheds
- Facade elements
- Fencing
- Batten boards

## Suitable For:

- Douglas wood
- Larch wood
- Spruce wood
- Pine wood
- Oak wood
- Scaffolding wood
- Treated wood
- Untreated wood

## Application On Untreated Wood:

1. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Sanding is not necessary, only when a smooth result is desired.
2. First clean greyed wood with [Lacq Wood Degreaser](#).
3. Clean with [Fluxaf Pro-Clean](#).
4. Stir the contents thoroughly.
5. Use a flat brush, roller, or airless paint sprayer. Apply in the longitudinal direction of the wood grain for a good finish.
6. Apply first coat.
7. The second coat can only be applied after complete drying.
8. We recommend applying 3 coats for optimal protection.

*Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance, and intensity of load. Always do a test area first to see if you get the desired finish and this will vary on different wood.*

## Surface Maintenance:

To make best use of the product, the surface should be cleaned and maintained annually. The surface can be cleaned by gently wiping it. Use a damp cleaning cloth or soft sponge for this purpose. Rough brushing and strong detergents should be avoided.

## Tools:

Flat brush or roller suitable for solvent-based paint.

## Coverage:

Approximately 12 m<sup>2</sup> per litre.

*Coverage always depends on the structure, porosity of the wood, layer thickness, the tools used and application conditions.*

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

**Drying time:**

Dust-dry:	Approx. 5-6 hours
Paintable:	Approx. 16 hours (depending on temperature).
Min. working temperature:	5 °C.
Max. processing temperature:	25 °C.

**Tool Cleaning:**

Clean tools with white spirit.

**Available Quantities:**

750 ml.

**Finish:**

Silk gloss.

**Available Colours:**

Available as standard in Natural, Impregnated, Brown & Black.

*Please note! The type of wood and the number of coats applied may influence the colour result. We therefore recommend always putting on a test area first to assess the result.*

**Shelf Life:**

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

**Safety Advice:**

Keep out of the reach of children. For detailed safety information, refer to the MSDS. MSDS can be downloaded at [www.lacq.eu](http://www.lacq.eu).

**Customised advice:**

For any advice, please contact the technical team on 0344 633 336.