

Fluxaf Wallpaper Remover

Fluxaf Wallpaper Remover is a powerful and effective solution for quickly and easily removing wallpaper. Whether it's paper, vinyl, or other types of wallpaper, this product makes wallpaper removal much simpler and prevents damage to the underlying wall. The formula is designed to soften and loosen the wallpaper from the wall, making the removal process quick and effortless. Fluxaf Wallpaper Remover is ideal for both large surfaces and smaller applications, and is the perfect choice for renovations and painting projects. The product is safe to use and ensures a clean, smooth wall, ready for a new finish.

Applicable on:

- Paper
- Vinyl
- Waterproof wallpaper (pierce layers well)

Instructions:

- 1. Prior to use: Cover floor covering, skirting boards & woodwork. Switch off power and ensure that wall sockets, switches and other voltage carrying objects are watertight.
- 2. Moisten the entire surface with a sprayer, block brush, or paint roller.
- 3. Keep the surface moist for at least 10 minutes.
- 4. Remove all loose wallpaper. Score through any stuck parts so that Fluxaf Wallpaper Remover can penetrate to the adhesive layer. For washable wallpaper with a PVC coating, first remove the PVC coating and/or score it.
- 5. Dilute Fluxaf Wallpaper Remover 1 parts to 5 with water and apply evenly to the surface using a block wiper or low pressure hand sprayer.
- 6. Leave Fluxaf Wallpaper Remover for 15-30 minutes and remove the soaked layers with a spatula.
- 7. If several layers are applied, the soaking time must be extended.
- 8. Ensure at all times that the cleaning agent does not dry out by wetting again and again.

Attention! Always do a test area first to see if you get the desired finish. Results can differ per wood or surface type.

Cleaning:

Clean tools with water.

Coverage:

Approx. 10-20 m² per litre of undiluted product.

Attention! Efficiency always depends on the surface type, the porosity of the wood, the layer thickness, the tools used and the application conditions.

Available quantities:

1 litre.

Shelf life:

At least 24 months, if stored in a dry, cool and frost-free place in uninterrupted, original packaging.

Safety advice:

For extensive safety information, consult the MSDS. MSDS can be downloaded at <u>www.fluxaf.nl</u>.